



COOLSPACE™
EVAPORATIVE COOLING

Operation and Maintenance Manual



GLACIER

TALL BASE

CS5-16-VD-TB
CS5-18-VD-TB2
120V/60HZ



MADE IN
THE USA





Operation & Maintenance Manual

Table of Contents:

1.0 Introduction	1
2.0 Unpacking your COOL- SPACE [®]	1
3.0 Set-up of COOL- SPACE [®] unit	1
3.1 Connecting the water supply	1
3.2 Connecting the electrical supply	2
4.0 Operating procedures	3
4.1 Filling the unit with water	3
4.2 Starting the fan	3
4.3 Starting the pump and adjusting the water flow	4
5.0 Maintenance and storage	4
5.1 Removing the cooling media & accessing the inside of the unit	4
5.2 Daily maintenance	4
5.3 Periodic maintenance	5
5.4 Storage	5
6.0 Troubleshooting/Repair	6
6.1 Troubleshooting	6 - 9
6.2 Repair procedures	10
6.3 Technical support	10
7.0 Warranty	11
7.1 Warranty form	11
7.2 Warranty parts	11
7.3 Optional accessories and replacement parts	11

Due to continuous product innovations, we reserve the right to change product specification without due notice.

Signal Word Definitions

 DANGER	DANGER indicates an imminently hazardous situation which, if not avoided, WILL result in death or serious injury.
 WARNING	WARNING indicates a potentially hazardous situation which, if not avoided, COULD result in death or serious injury.
 CAUTION	CAUTION indicates a potentially hazardous situation which, if not avoided, MAY result in minor or moderate injury.
IMPORTANT	IMPORTANT indicates a potentially hazardous situation which, if not avoided, MAY result in property damage.

1.0 Introduction

COOL-**SPACE**® is a patented and registered Trade Mark of Advanced Radiant Systems, Inc. and manufactured in Indiana.

The COOL-**SPACE**® unit is a compact, self-contained, high-efficiency portable evaporative cooler.

2.0 Unpacking your COOL-SPACE® unit

IMPORTANT

Carefully examine the carton for damage before opening. If the carton is damaged notify the shipping company immediately.

3.0 Set-up of the COOL-SPACE® unit

The COOL-**SPACE**® unit is factory tested and ready to use. The unit should be placed on a level surface, and the casters locked to prevent inadvertent movement. Follow instructions below to connect water and electrical supply.

3.1 Connecting the water supply

CAUTION

Do not connect the COOL-**SPACE**® unit to any water source where water pressure exceeds 120 psi. This will cause permanent damage to the unit.

The COOL-**SPACE**® unit comes equipped with a female garden hose water source connection. Attach the unit to a standard garden hose outlet for a water source. It is not recommended that the unit be attached to any water source with operating pressures above 120 psi. If you have not purchased the optional portable water tank; use a standard garden hose (not provided) to connect the tank to the cooler.

3.2 Connecting the electrical supply

IMPORTANT

The COOL-SPACE® unit should be plugged into a fused or circuit breaker protected 15 amp, 120 volt, and 60 Hz circuit.

All models utilize standard 120-volt power supply. The unit should be plugged into a fused or circuit breaker protected 15 amp, 120 volt, 60 Hz circuit. A ground fault circuit interrupter is included with every unit.

Table 1 shows the amperage requirements for the specific models. If an extension cord is required, refer to Table 2 for the proper 3-conductor heavy-duty cord required.

CAUTION

Do not exceed the amperage ratings of the extension cord. Undersized extension cords result in excessive drops in voltage, which cause the electric motors to generate excessive heat. This condition results in inefficient motor operation and premature motor failure, WHICH WILL VOID THE WARRANTY.

Table 1. Electrical requirements

CS Model Number	Volts ± 10%	Frequency (Hz)	Running Amps
16-VD	120	60	4.05

Table 2. Cord size requirement based on length and max amp draw

Length In Feet	Cord Size			
	16 Ga	14 Ga	12 Ga	10 Ga
0-50	13 A	18 A	25 A	30 A
50-100	10 A	13 A	18 A	25 A

A: Amps at 120 volt (de-rate for lower voltage)

4.0 Operating procedures

There are 3 factors to consider when determining where to place the COOL-SPACE® unit.

1. **Fresh air supply:** The inlet side of the unit (pad side) requires a constant, uninterrupted supply of fresh air for maximum performance. A distance of 3 feet clear space to any obstructions at the rear or inlet side of the unit is recommended.
2. **Discharge air flow:** The cool air discharged from the unit should be free of obstruction to allow the air to circulate in order to maximize the cooling zone.
3. **Ventilation:** In order to operate at maximum effectiveness, it is helpful to have provisions to remove the air discharged from the COOL-SPACE® unit from the cooling area. This ensures that the COOL-SPACE® unit does not recirculate air that has already been through the evaporative cooling process.

The COOL-SPACE® unit must be placed on a level surface to operate correctly. Units create an oval shaped air pattern. Obstacles such as racks and workbenches may interfere with the air flow. An attempt should be made to locate the unit in such a manner that interruption of the air pattern is held to a minimum. Multiple units may be required to cover larger areas.

When the COOL-SPACE® unit is placed near a wall or other vertical obstruction, it is recommended that there be a space of at least 3 feet between the back (pad side) of the unit and the obstruction. This ensures that a clear supply of fresh air is able to get to the inlet of the unit.

4.1 Filling the unit with water

Once the COOL-SPACE® unit has been connected to a water source as described in 3.1, turn the water supply valve on and the unit will fill with water. The float valve will shut off the water flow when the sump is full.

4.2 Starting the fan

Turn the fan switch to *HIGH* speed on start-up, allow motor to reach maximum speed, and then adjust to your preferred setting.

4.3 Starting the pump and adjusting the water flow

IMPORTANT

DO NOT flood the pads with water, keep them moist. New pads will take a few days before they become completely saturated. It is normal to have several dry streaks on the face of the pads about 1 to 2 inches wide. If the streaks are larger adjust the flow control knob to allow more water to flow onto the pads. NOTE: New pads may also emanate an odor under initial operating conditions from the resin used to construct the media. Flush the pads by running the pump without the fan running for at least 12 hours; overnight is best. Empty the sump and refill. Repeat if odor still exists.

NOTE: Run fan while adjusting the water flow

Once the sump is full, the pump switch may be turned to the 'ON' position. The flow control knob will need to be adjusted on initial start-up. It is located at the side of the unit; it controls the volume of water that is delivered to the top of the cooling pads.

CAUTION

Prolonged use of hard water without proper water treatment will create mineral deposit build up causing the pump to fail which is NOT COVERED BY WARRANTY

IMPORTANT

Pump is equipped with a **LOW WATER CUT OFF** which may take up to 5 minutes to reset each time.

5.0 Maintenance and storage

WARNING

ELECTRICAL SHOCK HAZARD

Disconnect the power supply before performing any service or maintenance on the unit. Failure to do so may result in serious injury or death.

5.1 Removing the cooling media to access the inside of the unit

In order to perform any maintenance on internal components, the cooling pads must be removed to access the inside of the unit.

1. Remove the (2) bolts connecting the pad retainer bar (pad-side) from the housing.
2. Tilt pads from the top; lift out of the unit.

Note: Reinstall pads correctly according to the markings on the pads.

5.2 Daily maintenance

IMPORTANT

When shutting down the COOL-SPACE® unit at the end of each use, the pump should be turned off approximately 15 minutes before the fan is turned off. This will allow the pads to drain and dry out. To avoid disfiguring the housing the unit should be drained after every use. These simple guidelines will ensure long and efficient pad life as well as help to control mildew and bacteria growth, and unit longevity.

5.3 Periodic maintenance

⚠ WARNING

ELECTRICAL SHOCK HAZARD

Disconnect the power supply before performing any service or maintenance on the unit. Failure to do so may result in serious injury or death.

Depending on how often the COOL-SPACE® unit operates, this procedure should be performed anywhere from every week for heavy use to monthly for light use. Shut down the unit and drain the water sump. The cooling pads act as a filtering agent and remove dust and other particles from the incoming air stream. These particles will flow into the sump and collect there. Also, impurities in the water will collect in the sump.

Draining the Water Sump

1. Close the water flow valve and open the drain valve.
2. Run pump until sump is dry then immediately shut off pump.
3. Turn unit off and disconnect the power supply.
4. Remove cooling pads, refer to section 5.1.
5. Clean out reservoir with either a towel or wet/dry vacuum.
6. Remove the water spray bar and its plug. Insure holes are free of debris.
7. Reinstall pads and pad retainer.

To keep the COOL-SPACE® unit operating at peak efficiency, ensure that the cooling pads are kept clean and dust-free. Dust and other particles have an adverse effect on the media's ability to introduce water into the air stream. If the pad surface becomes dirty or dusty, clean with a soft brush and water.

5.4 Storage

1. Remove the pads, as described in section 5.1
2. Clean with a soft brush and water to remove dust and debris
3. Drain sump using procedure described in section 5.3 and wipe dry
4. Store the COOL-SPACE® unit in a dry area. Cover if possible to prevent dust build-up.

6.0 Troubleshooting/Repair

6.1 Troubleshooting

WARNING

ELECTRICAL SHOCK HAZARD

Disconnect the power supply before performing any service or maintenance on the unit. Failure to do so may result in serious injury or death.

The COOL-**SPACE**[®] unit consists of three systems: the fan, water distribution and pump. It is important to determine which system of the COOL-**SPACE**[®] unit the problem is associated with. This may not always be obvious, in that certain problems may be associated with more than one system.

When determining which system has a problem, you must define the associated problem, (e.g. the pump is not running). Although this might seem a bit simplified, several things may cause this particular problem. So while defining the problem, a careful check of all systems should be made to fully understand the extent of the problem.

If you have a complete understanding of all of the systems of the COOL-**SPACE**[®] unit and how they depend on each other, it will be simple to define and solve any problem.

Necessary Tools:

Although the COOL-**SPACE**[®] unit is designed to be simple to maintain, it will be necessary to have some basic hand tools (screwdrivers, pliers, adjustable wrenches, etc.) as well as a volt/ohm meter when troubleshooting the electrical system.

6.1 Troubleshooting (continued)

Fan System

CAUTION

Please use caution when troubleshooting or repairing all electrical components. Be certain that all power is disconnected from the COOL-SPACE® unit before the cooling pads or fan guard are removed to gain access to the fan.

Direct Drive Models

Problem	Check	Solution
Fan won't run and makes no sound.	Power cord, extension cord, switches, circuit breaker, GFI ground fault.	Reconnect power or extension cord. Reset breaker.
Fan motor won't run and makes a humming sound.	Blade in contact with shroud. Motor stalled (will not turn by hand).	Re-center blade hub. Replace motor.
Breaker trips or fuse blows when fan is started.	Motor stall. Check power source for min. 120volt/15 amp. Extension cord.	Replace motor. Upgrade power supply. Replace with heavier cord.
Motor overheating and shutting off. Restarting several minutes later.	Extension cord gauge too small. Inlet air obstructed or too close to wall. Faulty motor.	Replace with heavier cord. Provide minimum 3 feet inlet clearance. Replace motor.
Fan motor won't run and switch makes soft clicking sound.	Switch making good contact.	Replace switch.
Fan blade doesn't turn and unit makes squealing sound.	Motor stall (as above).	Replace motor.
Fan will not reach speed but turns and makes humming sound.	Capacitor (where visible) and motor electrical connections. Extension cord too small.	Replace capacitor or motor. Increase cord gauge.

6.1 Troubleshooting (continued)

Water System

The water distribution system consists of two (2) assemblies:

- The Water Inlet Assembly
 - Brass bulkhead fitting
 - Float valve assembly

- The Hose and Valve Assembly
 - Spray Bar Assembly
 - Valve Assembly
 - Connection Hose

Problem	Check	Solution
Floor at side of COOL-SPACE® unit is wet	Water inlet hose is loose at supply hose or inlet hose is loose at bulkhead fitting.	Tighten connections and/or replace hose washers.
COOL-SPACE® unit overflows from reservoir or is spitting water through fan.	Float valve is loose. Water pressure is too high to allow float valve to shutoff (120psi max). Float valve is not seating properly.	Tighten connections and/or replace hose washers. Reduce water pressure by adding an inline reducer. Check all hoses for leaks.
Water spitting from the unit.	Flow control Cracked Hose & Valve Assembly. Hose connection loose	Reduce flow Replace Hose & Valve Assembly. Tighten hose.
Water leaking from drain valve.	For worn washer, worn stem. Make sure drain valve is closed	Replace washer. Replace drain valve.
Water leaking from water flow control valve.	Washer worn. Stem worn. Jam nut or lock nut loose.	Replace water flow control valve. Tighten Jam nut.
Too many dry streaks in the pads	Holes in spray bar blocked. Adjust water flow.	Remove spray bar. Remove plug and clean tube and holes. Open water flow control valve.

6.1 Troubleshooting (continued)

Pump

Problem	Check	Solution
Pump motor will not run when switch is turned on.	Turn fan on to check for power. Is water level high enough to make the low- water cut-off circuit?	If fan doesn't start; check breaker and cord plug-in. If fan does start; check for power to and through pump switch (when turned on). Fill water reservoir.
Pump motor hums when switch is turned on, but does not pump water.	Obstruction in impellor. Pump motor failure.	Remove object(s). Replace pump.
Pump makes loud noise while running.	Object(s) in impellor, impellor loose. Pump bearings bad.	Remove object(s). Replace pump.
Breaker trips or fuse blows when switch is turned on.	Check power cord length and breaker rating. Check for locked-up pump.	Refer to page 2 for unit amperage draw and to determine required cord gauge. Replace pump.
Pump won't run and power is available. Pump is functional.	Make certain switch is working. Is water level high enough to make the low- water cut-off circuit?	Replace switch if not completing circuit. Fill water reservoir enough to activate Low Water Shut-off switch.
Pump runs but does not pump water.	Air lock in outlet side of pump. Make certain the impellor is turning in pump.	Turn off and on to bleed. If not, replace pump.

6.2 Repair procedures

⚠ CAUTION

Repairs should be performed by a qualified technician!

⚠ WARNING

ELECTRICAL SHOCK HAZARD

Disconnect the power supply before performing any service or maintenance on the unit. Failure to do so may result in serious injury or death.

GLACIER (CS5-16-VD-TB) Fan Motor Replacement

1. Remove cooling pads (see section 5.1 for pad removal instructions)
2. Remove the black motor wiring plate and disconnect motor wires. (Mark each wire with a marker or marker tape to allow for easy matching when installing new motor.)
3. Remove the (4) nuts and bolts that mount the motor, fan, and support braces (complete fan assembly).
4. Replace new fan assembly.
5. Secure with 4 nuts and bolts.
6. Replace any wire ties that were removed when taking out the old fan assembly.
7. Replace the black motor wiring plate.
8. Reinstall pads and connect power

GLACIER (CS5-16-VD-TB) Pump Replacement

1. Loosen PVC Union
2. Remove pump and PVC pipe
3. Unplug the cord from the top of the pump by removing 2 screws
4. Unscrew PVC pipe from the pump
5. Reverse steps 1-4 to reinstall the new pump
6. Reinstall cooling pads and guards, reconnect power, and test pump

6.3 Technical support

Technical support and service are available directly from your distributor or

COOL-SPACE® Technical Support Line at 1-800-557-5716
Visit: www.cool-space.com Email: sales@cool-space.com

7.0 Warranty

Under normal use, the warranty covers the unit and its components for twenty-four (24) months from date of invoice. Refer to the manufacturer's Warranty Policy for details.

7.1 Warranty Form

You must register your COOL-SPACE® Portable Evaporative Cooler within fifteen (15) days of initial purchase to validate your cooler's warranty. You may fill out the warranty form supplied with your unit and fax it to 1-317-485-0118 or register online at www.cool-space.com.

7.2 Warranty parts

Warranty replacement parts are available through your local distributor or supplier where you purchased your COOL-SPACE® unit. If you have any questions or concerns, please contact us direct at 1-800-557-5716 or at sales@cool-space.com. Please have your **model number** and **serial number** ready.

IMPORTANT

DO NOT DISCARD FAULTY PARTS Check with the Manufacturer as they may need to be returned for warranty credit.

7.3 Optional Accessories and Replacement Parts

Accessories and replacement parts are available from your local distributor or supplier or they can be found online at www.cool-space.com.

Common GLACIER Replacement Parts

Fan Motor	
CS-F16-VD	GLACIER Variable Speed
Switches	
CS-E110	On/Off Pump
CS-E188-VD	Variable Speed
Pump	
CS-E163-2	GLACIER Pump
8" Pads	
CS-H610	CS5-16-VD-TB Pads for GLACIER (2 required)
Float Assembly	
CS-P142	Water Control Valve

For exploded view drawings please go to www.cool-space.com





COOL-SPACE™

EVAPORATIVE COOLING

315 N Madison Street
Fortville, IN 46040
1-800-557-5716
sales@cool-space.com

www.COOL-SPACE.com

